
Article number: 30.440.MB2.1 Printing possible

Storage bin type Euronorm - 400 x 300 x H 400 mm - closed - with picking opening on the long side - light grey





Product specifications

External dimensions (L x W x H)	400 × 300 × 400 mm
Internal dimensions (L x W x H)	366 × 266 × 385 mm
Capacity	37.5 liter
Handles	Open
Sidewalls	Closed
Material	PPC
Article number	30.440.MB2.1
Weight (kg)	1,8 kg
Temperature range	-20°C to +50°C, briefly up to +90°C
Color	Grey
Bottom	Closed, reinforced
European Article Number	7424912355363
Colorcode	RAL 7040
Gripping aperture size	290xH230 mm
Quantity per pallet	40

Properties

- **Euronorm storage bin, dimensions: 400 x 300 x H 400 mm**
- **Fully closed design - both walls and base**
- **Reinforced base design**
- **With picking opening on one long side**
- **Picking opening dimensions: 290 x H 230 mm**
- **Wall height below the picking opening: 122 mm**
- **Fitted with open handgrips**
- **Food-safe - for direct contact with foodstuffs**
- **Options: printing - lid - other picking opening dimensions**

TRANSOPLAST
Improves your Logistics

Transoplast
+31(0)314 66 44 00
website@transoplast.com
transoplast.com/wp

Description

Plastic stacking bin in **Euronorm format** 400 x 300 mm with a **picking opening on the long side**. The height including reinforced base is 400 mm. Thanks to the picking opening, the stacking bin is ideal for use as a storage bin. Due to its standardised dimensions, the stacking bin can be stacked with all other Euronorm stacking bins and is perfectly compatible with standardised pallets and mobile plastic trolleys. The stacking bin is food-safe, has a hygienic design and is fitted with two practical open handgrips. Designed with reinforced base. **Picking opening dimensions: 290 x H 230 mm**.

Matching accessories



30.400.SD.1



30.ZVK.00006



30.ZBS.00001



52.TR6040.4.H



52.TR6040.4.L



52.TR6040.4.K

Alternative articles



30.440.RDH.1



30.440.ROH.1



30.432.MB2.1



30.440.MB1.1

TRANSOPLAST
Improves your Logistics

Transoplast
+31(0)314 66 44 00
website@transoplast.com
transoplast.com/wp