Article number: 83330241 Printing possible

Industrial pallet / ISO pallet type CR3-5 ECO (1200 x 1000 x H 160 mm) - made from ECO regranulate - with 5 skids - with 5 mm raised rims all around.







Product specifications

External dimensions (L x W x H)	1200 × 1000 × 160 mm
Dynamic load capacity	1250 kg
Material	Recycled ECO-HDPE
Article number	83330241
Weight (kg)	21,5 kg
Temperature range	-30°C to +40°C, briefly up to +90°C
Color	Black
Static load capacity	5000 kg
Edge height	5 mm
Load capacity in racks	1000
Quantity per pallet	15

Properties

- **Very robust pallet in a basic configuration**
- **Racking load capacity: 1,000 kg**
- **Made from ECO regranulate and without anti-slip strips on the deck, making it more attractively priced**
- **Thanks to the high-quality regranulate composition, there are virtually no compromises in impact resistance**
- **Equipped with 5 skids - 3 longitudinal and 2 transverse**
- **Underside of the blocks and skids is ribbed - for increased grip in automated storage and conveyor systems**
- **Deck fitted with 5 mm raised rims all around**
- **Skids are chamfered on both sides - for easy handling with hand pallet trucks, etc.**
- **Suitable for applications with packaged food**
- **Marking, logos and numbering on request; position to be agreed**
- **Options: pallet lid / pallet cover - pallet collars - QR codes and barcodes - RFID transponders - top deck without rims or with 7 mm rims**

TRANSOPLAST
Improves your Logistics

Transoplast
+31(0)314 66 44 00
website@transoplast.com
transoplast.com/wp

Description

The CR3-5 industrial pallet with 5 skids is a robust and versatile plastic pallet for heavy internal and industrial applications - including in the food industry. The pallet is equipped with five skids - three longitudinal and two transverse - making it ideal for automated storage and transport systems. The underside of the skids and the blocks is ribbed, optimising grip in these systems.
This CR3-5 pallet is made from ECO regranulate. A controlled stream of HDPE plastic is regranulated and reprocessed to a high standard. The result is a plastic pallet that, in terms of load capacity and impact resistance, performs almost on a par with virgin quality. However, an ECO pallet is more attractively priced because recycled plastic is used.
In addition, the anti-slip strips on the deck have been omitted on this version. This is not an issue when the 5 mm raised rims provide sufficient centring of loads and of empty pallets when stacked. This also contributes to a lower product price.
The CR3-5 ECO is fitted with 5 skids. This enables block stacking, i.e. stacking loaded pallets directly on top of each other. Naturally, this requires even and stable support. In addition, skids all around are required in various automated systems - especially when pallets are transferred sideways.

Matching accessories



99.49716




83291800

Alternative articles



87030840



83332202

Transoplast
+31(0)314 66 44 00
website@transoplast.com
transoplast.com/wp