Article number: 30.428.DB.1-2 Printing possible

Ballot box with letterbox flap and lock - 400 x 300 x H 295 mm - grey - equal lock







Product specifications

External dimensions (L x W x H)	400 × 300 × 295 mm
Internal dimensions (L x W x H)	356 × 256 × 260 mm
Max. stacking load (kg)	150 kg
Capacity	26 liter
Handles	Closed
Sidewalls	Closed
Material	PPC
Article number	30.428.DB.1-2
Weight (kg)	2,25 kg
Temperature range	-20°C to +50°C, briefly up to +90°C
Color	Grey
Bottom	Closed, reinforced
Type of lock	Keyed alike cylinder lock (the provided key opens multiple cylinders)
Load capacity (kg)	25
Quantity per pallet	64
Stacking height (mm)	282

Properties

- **Grey ballot box with hinged lid from the SOLID LINE. Dimensions: 400 x 300 x H 295 mm - 26 liter**
- **Equipped with equal lock cylinder lock (including two keys)**
- **The supplied keys open multiple cylinder locks**
- **The lid is fitted with a letterbox flap with an effective insertion slot of 280 x 32 mm (l x w)**
- **The letterbox flap opens outwards and is made of anodised aluminium**
- **The hinges are fitted with stainless steel hinge reinforcements**
- **The ballot boxes can be stacked with each other, as well as with other Euronorm bins - with or without a lid**
- **Fully closed design - both the walls and the base**
- **With closed handgrips - for optimal volume utilisation and to optimally protect the contents**
- **The base is reinforced**
- **Mainly used for collecting confidential data**
- **Food-safe and hygienically designed**
- **Options: printing - hinged lids in another colour - other bin colour - single lock version - version with insertion slot**

TRANSOPLAST
Improves your Logistics

Transoplast
+31(0)314 66 44 00
website@transoplast.com
transoplast.com

Description

Ballot box from the SOLID LINE

Plastic ballot box or transport box with hinged lid and two snap-slide closures; in Euronorm format (400 x 300 x H 295 mm - 26 liter). Finished in a neutral grey colour and part of our SOLID LINE - a modern stacking bin range with rounded corners and minimal ribbing. The ballot box is lockable and a spring-loaded letterbox flap is integrated into the lid.

Applications

The ballot box is primarily used by government institutions to collect ballot papers. In addition, staff associations and boards also use ballot boxes for voting. Ballot boxes are also used as suggestion boxes, for timesheets and for doctor's prescriptions or other medical forms. In all cases, confidential data is being collected. That is why the ballot boxes are lockable and fitted with a hinged flap.

Product details

Thanks to the standardised dimensions (400 x 300 mm), the ballot boxes or transport boxes can be stacked with all other Euronorm stacking bins - with or without a lid. The ballot box is food-safe, has a hygienic design and is fitted with two closed handgrips for optimal volume utilisation and optimal protection of the contents. Designed with a reinforced base. The ballot box is fitted with a spring-loaded letterbox flap integrated into the lid. The insertion slot measures 280 x 32 mm (l x w). The ballot box is also equipped with an equal lock cylinder lock. The supplied keys therefore open multiple cylinder locks with an identical lock.

Matching accessories

4541.830



52.TR6040.4.K



52.RC682D.ZABV.2

Alternative articles



30.632.KO.1-1



30.424.DB.1-4



30.424.DB.1-3



30.632.KO.1-2



30.632.KO.1-3



30.642.KO.1-2

Transoplast
+31(0)314 66 44 00
website@transoplast.com
transoplast.com