Article number: 30.927.00.A Printing possible

Bottle crate 300 x 200 x H 304 mm - 6 compartments - black







Product specifications

External dimensions (L x W x H)	300 × 200 × 304 mm
Internal dimensions (L x W x H)	278 × 180 × 288 mm
Handles	Open
Sidewalls	Perforated
Material	Recycled HDPE
Article number	30.927.00.A
Weight (kg)	1,09 kg
Temperature range	-30°C to +40°C / briefly up to +90°C
Color	Black
Bottom	Perforated
Maximum glass height	280
Maximum Ø glass	92
Stacking height (mm)	300

Properties

- **Fully perforated bottle crate. Dimensions 300 x 200 x H304 mm**
- **Equipped with a fixed 6-compartment divider**
- **Suitable for up to six bottles or jars Ø 92 mm – maximum height 280 mm**
- **For organised storage and safe transport**
- **Compact crate format for space-saving storage**
- **Temperature resistant from -30 °C to +40 °C / briefly up to +90 °C**
- **Suitable for packaged food products**

TRANSOPLAST
Improves your Logistics

Transoplast
+31 314 664400
website@transoplast.com
transoplast.com/wp

Description

Plastic bottle crate (300 x 200 x H304 mm) in black. **Equipped with a fixed 6-compartment divider** for bottles or jars with a **maximum diameter of 92 mm** and a **maximum height of 280 mm**.

Application


Suitable for organised storage and safe transport of up to six bottles or jars. The **integrated compartment divider** keeps the bottles and jars separated and **reduces the risk of damage** during transport.

Product details


The individual compartments measure 92 x 92 mm and are suitable for bottles and jars with a maximum height of 280 mm. Thanks to the four open hand grips, the bottle crate can be easily lifted and carried from all sides. Its compact footprint also enables efficient storage where space is limited.

The bottle crate is made from robust recycled HDPE. The recycled material is wear-resistant and suitable for use with packaged food products. Our bottle crates are used intensively every day in warehouses, production environments and during transport, both at ambient and refrigerated temperatures. The crate is temperature resistant from -30 °C to +40 °C and can withstand temperatures of up to +90 °C for short periods.

Matching accessories



52.RC682D.ZBV.2



87065899



83102217TP



52.TRR6040.4.H

Alternative articles



30.902.00.A



30.925.00.A

Transoplast
+31 314 664400
website@transoplast.com
transoplast.com/wp