
Article number: 8.1208CD.ESD Printing possible

Euro pallet 1208CD.ESD - 1200 × 800 mm - with 5 mm rims - 3 pallet runners - fully closed deck - ESD version: electrically conductive plastic - black







Product specifications

External dimensions (L x W x H)	1200 × 800 × 150 mm
Dynamic load capacity	1000 kg
Article number	8.1208CD.ESD
Weight (kg)	15 kg
Color	Black
Surface resistance	1 × 10^3 – 1 × 10? ? (according to IEC 61340-2-3)
Static load capacity	3000 kg
Edge height	5 mm
Load capacity in racks	500
Quantity per pallet	16

Properties

- **Plastic medium pallet in Euro size with 3 pallet runners**
- **Electrostatic dissipative (ESD): protects sensitive parts against build-up and electrostatic discharge, which can damage sensitive electronics**
- **Fully closed deck to prevent contamination from the floor and for easy cleaning**
- **Deck with 5 mm rims all around for centring the load and aligning empty pallets when stacked**
- **Marking, logos and numbering on request. Location by arrangement**
- **Options: pallet lid / pallet cover - QR codes and barcodes - RFID transponders**

Description

This plastic Euro pallet is produced from polypropylene (PP) with an ESD compound. This gives the pallet electrically conductive properties, preventing electrostatic build-up and subsequent discharge. Such a discharge can damage sensitive electronics.
The 1208CD features a closed deck. This shields the underside of the pallet load from dust and dirt from the floor. It also makes the pallet easier to clean. The deck is fitted with 5 mm rims all around for centring the load and for aligning empty pallets when stacked. For improved grip, the deck surface is slightly uneven with a textured finish.

TRANSOPLAST
Improves your Logistics

Transoplast
+31 314 664400
website@transoplast.com
transoplast.com/wp

TRANSOPLAST
Improves your Logistics

Transoplast
+31 314 664400
website@transoplast.com
transoplast.com/wp