




Euro pallet CS1 - 1200 x 800 mm - without rims - 3 pallet skids, open with reinforcement ribs - light grey



Product specifications

External dimensions (L x W x H)	1200 × 800 × 145 mm
Dynamic load capacity	1000 kg
Material	HDPE
Article number	83190800
Weight (kg)	12,3 kg
Temperature range	-30°C to +40°C / briefly up to +90°C
Color	Grey
Static load capacity	5000 kg
Load capacity in racks	400
Quantity per pallet	16

Properties

The CS1 is a medium-duty Euro pallet that can be configured modularly

This CS1 is a version without raised edges. This special variant is used in the paper industry and as a base for welded pallets with non-standard dimensions.

The CS1 is produced from new virgin HDPE granulate with top product quality. The base material is highly impact resistant and offers a long service life.

The CS1 is suitable for direct contact with food products.

The racking load capacity is 400 kg

Marking, logos or numbering on request; location to be agreed

Options: closed pallet skids - corrosion-resistant reinforcement profiles (max. 4) - QR codes and barcodes - RFID transponders - Palgrip anti-slip under the skids - ESD version - version with 7 mm deck rims or with 22 mm rims along the deck - pallet lid / pallet cover - fit-on rims

Description

The CS1 Euro pallet is a medium-duty pallet that can be configured modularly, making it suitable for almost any application. The CS1 pallet is supplied as standard without raised rims. The pallet is always produced from new virgin HDPE granulate with top product quality. Thanks to the new high-quality HDPE, the pallet is particularly robust and impact resistant, with a long service life. As a result, the CS1 can be offered at an attractive price - that is the base.

Optional:

The 3 skids of the CS1 can be produced completely smooth and closed. This provides optimum hygiene. In addition, it makes the skids particularly robust, with higher load capacity and smooth running on roller conveyors.

The racking load capacity of the base version is 400 kg. Thanks to its modular design, the CS1 can also be configured for higher loads. The pallet deck can be reinforced with reinforcement profiles. By fitting up to 4 corrosion-resistant reinforcement profiles - immediately or later - the CS1 can easily be upgraded from a medium-duty pallet to a true racking pallet with a load capacity of up to 1400 kg.

The CS1 can also be produced with 7 mm rims on the topdeck and also as a version with 22 mm rims positioned along the pallet deck. This keeps the usable deck size at 1200 x 800 mm. VDA-KLT automotive containers, with their different base dimensions, require this.

For use in automated warehouses, for example where driven rollers and braking rollers are used, the CS1 closed skids can optionally be equipped with anti-slip.

For tracking and tracing, CS1 pallets can be equipped with RFID transponders. These can also be retrofitted without any issues.

For applications involving sensitive electronics, CS1 pallets can be supplied as an ESD version as standard. These pallets have electrically conductive properties, preventing electrostatic build-up and harmful discharge.

In short, the CS1 has a stable base that can be fully customised for a wide range of applications. This ensures the pallet is never over-engineered and can also be offered at an attractive price.



Matching accessories



Alternative articles

