

Article number: 83192201

Printing possible



Euro pallet CS1-L - 1200 x 800 mm - with 7 mm rims - 3 pallet skids, open with reinforcement ribs - black ESD



Product specifications

External dimensions (L x W x H)	1200 x 800 x 150 mm
Dynamic load capacity	1000 kg
Material	Comp 25 (ESD)
Article number	83192201
Weight (kg)	14 kg
Temperature range	-30°C to +40°C, briefly up to +90°C
Color	Black
Surface resistance	10 ⁷ ohms (according to DIN 53428 / IEC 60093)
Static load capacity	5000 kg
Edge height	7 mm
Load capacity in racks	400
Quantity per pallet	16

Properties

Electrostatic dissipative (ESD): protects sensitive components against charge build-up and electrostatic discharge

Undersides of blocks and pallet skids are open with reinforcement ribs

Raised rims around the deck of the CS1-L prevent loads from slipping and prevent empty pallets from sliding on each other

The CS1-L is extra strong thanks to the robust connection between the skids and the blocks

Optional fully welded (closed) skids increase the pallet's strength and impact resistance

Marking, logos or numbering on request; location to be agreed

Options: Pallet lid / pallet cover - QR codes and barcodes - RFID transponders - closed skids - version without rims, with 7 or 22 mm deck rims, with 22 mm side rims along the deck

Description

Our ESD pallets are produced from high-quality plastic to which an ESD compound is added. This gives the pallet electrically conductive properties. It prevents electrostatic build-up and subsequent discharge, which can damage sensitive electronics. The CS1-L is designed for efficient transport of Euro standard stacking bins (ESD version). For additional centring of a full pallet load with stacking bins, we supply a 1200 x 800 mm pallet lid in an ESD version.



Alternative articles

