
Article number: 83241880 Printing possible

Euro pallet EURO L1 – 1200 x 800 mm – without rims – 3 pallet runners with anti-slip – pallet deck with anti-slip







TRANSOPLAST
Improves your Logistics

Transoplast
+31 314 664400
website@transoplast.com
transoplast.com/wp

Product specifications

External dimensions (L x W x H)	1200 × 800 × 150 mm
Dynamic load capacity	1250 kg
Material	HDPE
Article number	83241880
Weight (kg)	20 kg
Temperature range	-30°C to +40°C, briefly up to +90°C
Color	Grey
Static load capacity	7500 kg
Load capacity in racks	1250
Quantity per pallet	16

Properties

- **The EURO L1 is a heavy-duty pallet in a class of its own. Made from high-quality virgin plastic. Food-safe with high impact resistance.**
- **Equipped with 3 pallet runners lengthwise. The underside of the runners is hygienically closed and fitted with wear-resistant Palgrip anti-slip soles.**
- **These anti-slip pallet runners provide grip in automated transport systems.**
- **The pallet deck is reinforced with 5 corrosion-resistant reinforcement profiles that are fully integrated - hermetically enclosed beneath the anti-slip strips.**
- **Anti-slip strips on the pallet deck prevent loads from shifting - also in moist environments.**
- **The pallet runners are perfectly flat and straight, without steps - for smooth running on conveyor belts.**
- **Extra strong thanks to the angled connections between the blocks, the runners and the deck.**
- **The pallet runners are chamfered on both sides, allowing the pallet to be handled easily.**
- **With profiled corner blocks for better grip of wrapping and stretch film.**
- **High load capacity in pallet racking up to 1250 kg.**
- **The EURO L1 dimensions match those of wooden Euro pallets - including the pallet height. Use in systems designed for this is therefore possible.**
- **Particularly suitable for automated logistics processes and pallet shuttle systems, where excessive deflection of pallets or runners can cause malfunctions.**
- **Engineered for an exceptionally long service life and high ease of use.**
- **Marking, logos and numbering on request. Position by arrangement.**
- **Options: pallet lid/palletcover - pallet collars - with 7 mm rims on the deck - QR codes and barcodes - RFID transponders - Palgrip anti-slip clips (for under the deck)**

Transoplast
+31 314 664400
website@transoplast.com
transoplast.com/wp

Description

Our EURO L1 is the ultimate plastic Euro pallet. A heavy-duty pallet in a league of its own that will make the heart of every logistics manager beat faster. First of all, the pallet body is produced in one piece and engineered to be exceptionally robust. This gives it extremely high impact resistance. In addition, the 3 pallet runners are also injection-moulded in one piece. They form an integral part of the pallet and are additionally fitted with thick Palgrip anti-slip soles. These are welded underneath the runners. Besides providing anti-slip performance, this results in a virtually wear-free pallet runner that is also highly hygienic. Because the runners are completely flat, trouble-free use on all common internal transport systems is guaranteed. Combined with a super-strong pallet deck incorporating 5 reinforcement profiles, this creates a plastic pallet with minimal deflection - an important factor in automated warehouses with tight tolerances. The wear-resistant anti-slip soles on the underside of the pallet runners contribute to disruption-free internal logistics. The top side of the pallet deck is also equipped with anti-slip strips. This prevents loads from shifting, even when tilted or in wet conditions. All in all, the EURO L1 is a plastic pallet where everything has been thought of. With a pallet height of 150 mm, the EURO L1 can even be used in systems where wooden EURO pallets are also deployed. In addition to these multifunctional features, the EURO L1 has one key fundamental characteristic: an extremely long service life, without disruptions. Something that is essential in logistics, but often hard to find.

Matching accessories



99.49715



99.61660




82550801




83290800

Alternative articles



87065899



83341881

Transoplast
+31 314 664400
website@transoplast.com
transoplast.com/wp