Article number: 30.632.MB2.1 Printing possible

Storage bin type Euronorm - 600 x 400 x H 320 mm - closed - with picking opening on the long side - light grey







Product specifications

External dimensions (L x W x H)	600 × 400 × 320 mm
Internal dimensions (L x W x H)	566 × 366 × 305 mm
Capacity	64 liter
Handles	Open
Sidewalls	Closed
Material	PPC
Article number	30.632.MB2.1
Weight (kg)	2,8 kg
Temperature range	-20°C to +50°C, briefly up to +90°C
Color	Grey
Bottom	Closed, reinforced
European Article Number	7424905640698
Colorcode	RAL 7040
Gripping aperture size	490xH150 mm
Quantity per pallet	28

Properties

- **Euronorm storage bin, dimensions: 600 x 400 x H 320 mm**
- **Fully closed design - both walls and base**
- **Reinforced base design**
- **With picking opening on one long side**
- **Picking opening dimensions: 490 x H 150 mm**
- **Wall height below the picking opening: 122 mm**
- **Fitted with open handgrips**
- **Food-safe - for direct contact with foodstuffs**
- **Options: printing - lid - other picking opening dimensions**

TRANSOPLAST
Improves your Logistics

Transoplast
+31(0)314 66 44 00
website@transoplast.com
transoplast.com

Description

Plastic stacking bin in **Euronorm format** 600 x 400 mm with a **picking opening on the long side**. The height including reinforced base is 320 mm. Thanks to the picking opening, the stacking bin is ideal for use as a storage bin. Due to its standardised dimensions, the stacking bin can be stacked with all other Euronorm stacking bins and is perfectly compatible with standardised pallets, mobile plastic trolleys or roll containers. The stacking bin is food-safe, has a hygienic design and is fitted with two practical open handgrips. Designed with reinforced base. **Picking opening dimensions: 490 x H 150 mm**.

Matching accessories



30.ZBS.00001



30.ZVK.00006



52.TR6040.4.R



30.600.SD.1



52.TR6040.4.K



52.TR6040.4.L

Alternative articles



30.632.MB1.1



30.632.ROH.1



30.632.RDH.1

TRANSOPLAST
Improves your Logistics

Transoplast
+31(0)314 66 44 00
website@transoplast.com
transoplast.com