Article number: 3648.005.102 Printing possible

Stacking bin - 600 x 400 x H 89 mm - closed handgrips - white



Product specifications

External dimensions (L x W x H)	600 × 400 × 89 mm
Internal dimensions (L x W x H)	555 × 355 × 86 mm
Capacity	16 liter
Handles	Closed
Sidewalls	Closed
Material	HDPE
Article number	3648.005.102
Weight (kg)	1,2 kg
Temperature range	-30°C to +40°C, briefly up to +90°C
Color	White
Bottom	Closed, smooth
Quantity per pallet	108
Stacking height (mm)	77

Properties

- **Heavy-duty stacking bin for intensive use. Dimensions 600 x 400 x H 89 mm**
- **Usable internal height when stacked: 74 mm**
- **Suitable for a wide range of applications in industry and skilled trades, as well as in hospitality, catering and logistics**
- **Fully closed design - both walls and base**
- **With closed handgrips - for optimal use of volume and protection against dust and other external influences**
- **The base is completely smooth and flat for optimal hygiene**
- **Food-safe and hygienically designed**
- **Options: printing - coversheets**

Description

Plastic **stacking bin** in **Euronorm format** (**600 x 400 x H 89 mm** - 16 liter). **Heavy-duty version for intensive use**, in white. Users can be found in industry and skilled trades, as well as in hospitality, catering and logistics.
Thanks to its **standardised dimensions** (600 x 400 mm), the stacking bin can be **stacked with all other Euronorm stacking bins** and is **perfectly compatible** with **standardised pallets**, **transport trolleys** and **roll containers**.
The stacking bin is food-safe, features a **hygienic design** and is fitted with two closed handgrips - for optimal use of the internal volume and to help protect the contents from external influences. Fitted with a **hygienically smooth base** on the underside.
Everything for efficient logistics.

TRANSOPLAST
Improves your Logistics

Transoplast
+31(0)314 66 44 00
website@transoplast.com
transoplast.com

Matching accessories



89.E3

4541.830



30.090.D00

Alternative articles



52.RC682H.ZABV.2



52.TR6040.4.K



83100801

Transoplast
+31(0)314 66 44 00
website@transoplast.com
transoplast.com