Article number: 83170801 Printing possible

Half Euro pallet H2 - 800 x 600 mm - with 7 mm raised rims - without locating lugs on the deck - grey







Product specifications

External dimensions (L x W x H)	800 × 600 × 160 mm
Dynamic load capacity	500 kg
Material	HDPE
Article number	83170801
Weight (kg)	9 kg
Temperature range	-30°C to +40°C, briefly up to +90°C
Color	Grey
Static load capacity	2000 kg
Edge height	7 mm
Quantity per pallet	30

Properties

- **The H2 pallet (800 x 600 mm) has the dimensions of a true half Euro pallet**
- **Our H2 pallet stacks perfectly on its larger counterpart, the EURO H1 - 2 units per layer**
- **7 mm raised rims prevent loads from sliding off and empty pallets from sliding against each other**
- **H2 pallets have an open underside and are fitted with reinforcement ribs**
- **Thanks to their design, H2 pallets are 2-way entry - from both long sides**
- **Suitable for direct food contact**
- **Marking, logos or numbering on request; location to be agreed**
- **Options: pallet lid / pallet cover - locating lugs on the deck (for stackable bins) - version without rims - QR codes and barcodes**

TRANSOPLAST
Improves your Logistics

Transoplast
+31(0)314 66 44 00
website@transoplast.com
transoplast.com

Description

Our H2 pallet is a half Euro pallet (800 x 600 mm) in the truest sense of the word. The H2 is exactly half the size of its Euro-format counterpart - our EURO H1. The design of the H2 ensures it stacks safely on the EURO H1. Thanks to precisely matched stacking lugs and rims, two H2 pallets are securely centred on the EURO H1. They will not slide off under any circumstances - this has been carefully engineered.

The H2 pallet is fitted with raised rims all around. This makes it highly suitable for transporting stackable bins. The food industry, in particular, is a key user of this pallet.

The H2 pallet is produced from virgin HDPE, making it suitable for direct food contact and exceptionally impact resistant. We call it “virtually indestructible”.

Alternative articles



55.QP6080L3RR



83512201



83200801



83100800

Transoplast
+31(0)314 66 44 00
website@transoplast.com
transoplast.com