



Industrial / ISO pallet CS3-L - 1200 x 1000 mm - with 7 mm rims - 3 pallet skids, open with reinforcement ribs - black ESD



Product specifications

| | |
|----------------------------------|-------------------------------------|
| External dimensions (L x W x H) | 1200 x 1000 x 150 mm |
| Dynamic load capacity | 1000 kg |
| Material | HDPE with carbon compound |
| Article number | 83222201 |
| Weight (kg) | 15,2 kg |
| Temperature range | -30°C to +40°C, briefly up to +90°C |
| Color | Black |
| Surface resistance | ?1x10 E4 Ohm to 1x10 E11 Ohm |
| Static load capacity | 5000 kg |
| Edge height | 7 mm |
| Load capacity in racks | 400 |
| Quantity per pallet | 16 |

Properties

Electrostatic dissipative (ESD): protects sensitive components against charge build-up and electrostatic discharge

Undersides of blocks and pallet skids are open with reinforcement ribs

Raised rims around the deck of the CS3-L prevent loads from slipping and prevent empty pallets from sliding on each other

The CS3-L is extra strong thanks to the robust connection between the skids and the blocks

Optional fully welded (closed) skids increase the pallet's strength and impact resistance

Marking, logos or numbering on request; location to be agreed

Options: Pallet lid / pallet cover - QR codes and barcodes - RFID transponders - closed skids - version without rims, with 7 or 22 mm deck rims, with 22 mm side rims along the deck

Description

Our ESD pallets are produced from high-quality plastic to which an ESD compound is added. This gives the pallet electrically conductive properties. It prevents electrostatic build-up and subsequent discharge, which can damage sensitive electronics. The CS3-L is designed for efficient transport of Euro standard stacking bins (ESD version). For additional centring of a full pallet load with stacking bins, we supply a 1200 x 1000 mm pallet lid in an ESD version.



Alternative articles

