Article number: 83182222 Printing possible

Industrial pallet H3-L - 1200 x 1000 mm - with 7 mm rims - 3 open pallet skids - black ESD







Product specifications

External dimensions (L x W x H)	1200 × 1000 × 160 mm
Dynamic load capacity	1250 kg
Material	HDPE with carbon compound
Article number	83182222
Weight (kg)	21,5 kg
Temperature range	-30°C to +40°C, briefly up to +90°C
Color	Black
Surface resistance	?1x40 E4 Ohm to <1x10E11 Ohm
Static load capacity	5000 kg
Edge height	7 mm
Load capacity in racks	850
Quantity per pallet	15

Properties

- **Electrostatic dissipative (ESD): protects sensitive components against charge build-up and electrostatic discharge**
- **Undersides of blocks and pallet skids are open (ribbed)**
- **Raised rims around the deck of the H3-L prevent loads from slipping and prevent empty pallets from sliding on each other**
- **The H3-L is extra strong thanks to the robust connection between the skids and the blocks**
- **Marking, logos or numbering on request; location to be agreed**
- **Options: Pallet lid / pallet cover - QR codes and barcodes - RFID transponders**

Description

Our ESD pallets are produced from high-quality plastic to which an ESD compound is added. This gives the pallet electrically conductive properties. It prevents electrostatic build-up and subsequent discharge, which can damage sensitive electronics.
The H3-L pallet is designed for efficient transport of Euro standard stacking bins (ESD version). For additional centring of a full pallet load with stacking bins, we supply a 1200 x 1000 mm pallet lid in an ESD version.

TRANSOPLAST
Improves your Logistics

Transoplast
+31(0)314 66 44 00
website@transoplast.com
transoplast.com

Matching accessories



83292210

Alternative articles



83192201



83222201



83102222

Transoplast
+31(0)314 66 44 00
website@transoplast.com
transoplast.com