Article number: 87030204 Printing possible

Industrial pallet TC3-5 ECO - 1200 x 1000 mm - with 7 mm rims - 5 pallet skids - black







TRANSOPLAST
Improves your Logistics

Transoplast
+31(0)314 66 44 00
website@transoplast.com
transoplast.com

Product specifications

External dimensions (L x W x H)	1200 × 1000 × 160 mm
Dynamic load capacity	1500 kg
Material	Recycled ECO-HDPE
Article number	87030204
Weight (kg)	22,5 kg
Temperature range	-30°C to +40°C, briefly up to +90°C
Color	Black
Static load capacity	7500 kg
Edge height	7 mm
Load capacity in racks	1250
Quantity per pallet	15

Properties

- **The TC3-5 ECO is produced from high-quality ECO regranulate**
- **ECO pallets can be used with packed food products**
- **Equipped with 5 pallet skids: 3 longitudinal and 2 transverse. This allows loaded pallets to be stacked on top of each other while maintaining proper support**
- **Top and underside of the pallet deck are completely smooth and closed**
- **Maximum cleanability and hygiene**
- **Manual cleaning is possible without difficulty**
- **High impact resistance thanks to the patented welding of the top deck**
- **The high-grade regranulate quality ensures a homogeneous weld result and excellent pallet quality**
- **Pallet loads and empty pallets are secured and centred by 7 mm raised rims**
- **High racking load capacity up to 1000 kg**
- **By using 3 fully integrated reinforcement profiles in the pallet deck (longitudinal), the racking load capacity can be increased to up to 2000 kg (on request)**
- **With profiled block corners for better grip of stretch and wrapping film**
- **Marking, logos and numbering on request; position to be agreed**
- **Options: Pallet lid / pallet cover - fit-on rims - QR codes and barcodes - fully integrated metal inserts (longitudinal) - RFID transponders - top deck without rims, with 22 mm deck rims - fully Palgrip anti-slip top deck (virgin)**

Transoplast
+31(0)314 66 44 00
website@transoplast.com
transoplast.com

Description

Our TC3-5 ECO is a 1200 x 1000 mm industrial pallet on 5 skids. This pallet variant is part of the TC pallet family - the absolute top performers on the market when it comes to cleanability and hygiene.
TC pallets are “Totally Closed”, i.e. completely smooth and closed. For this reason, this pallet series is widely used in the food industry, pharmaceuticals and the chemical industry.
The ECO regranulate version is a high-quality recycled pallet that is often used in the high-tech sector, for example in cleanrooms and other technical production environments. Here too, easy cleaning is crucial. In addition, this ECO pallet is widely used for supply into the food sector, for example for packaging. Thanks to the high-quality regranulate, the TC3-5 ECO is produced with a very homogeneous weld result and excellent product quality. As a result, the TC3-5 in ECO material offers outstanding impact resistance and high load capacity — even comparable to a pallet made from virgin material. However, the price of an ECO pallet is more attractive because recycled plastic is used.
The TC3-5 is equipped with 5 pallet skids. This allows block stacking, i.e. stacking loaded pallets on top of each other. In addition, skids all around are sometimes required in automated systems.
Among the pallets available on the market with a completely smooth and closed deck, the TC pallet is the number 1 in terms of impact resistance. This is achieved through the patented welding of the top deck, with maximum wall thicknesses and a smart impact zone. The connection between the pallet blocks and the skids is also reinforced to the maximum. Everything for a long service life and sustainable use.
The pallet deck is fitted with 7 mm raised rims all around. In most cases this is sufficient to centre loads and pallets stacked on top of each other. Practical tests are the best benchmark here. If maximum anti-slip is required, our Palgrip variant with anti-slip top deck is the best solution.

Matching accessories



83291800



99.49716

Alternative articles



87035841.DUO



87030840

Transoplast
+31(0)314 66 44 00
website@transoplast.com
transoplast.com