Article number: 10.3.930.2

Insert bin 1/4 (length) type PRO for 600 x 400 mm - 554 x 88 x H 99 mm - grey







Product specifications

External dimensions (L x W x H)	554 × 88 × 99 mm
Internal dimensions (L x W x H)	548 × 71 × 93 mm
Handles	Internal grab rims
Sidewalls	Closed
Material	PP
Article number	10.3.930.2
Weight (kg)	0,3 kg
Temperature range	-20°C to +50°C, briefly up to +90°C
Bottom	Closed

Properties

- **Plastic insert bin type PRO (554 x 88 x H 99 mm) - in 1/4 format, lengthwise**
- **For Euronorm stacking bins 600 x 400 mm - from an external height of 120 mm**
- **Easy to remove thanks to the internal grip edge**
- **Suitable for use in Euronorm cases 600 x 400 x H 135 mm - with a foam sheet in the hinged lid**
- **Four PRO insert bins in 1/4 format fit into 600 x 400 mm stacking bins - lengthwise**
- **Made from food-safe plastic - for direct contact with unpackaged food**
- **Options: version as a case with insert bins**

Description

Robust plastic insert bin **type PRO** (554 x 88 x H 99 mm) for use in Euronorm stacking bins **600 x 400 mm**. **1/4 format - lengthwise**; allowing two insert bins to be placed in each stacking bin. It can of course also be combined with other PRO formats.

Application

With PRO insert bins, you can easily create a subdivision in stacking bins. PRO insert bins are removable and stackable with each other. The insert bins are suitable for use in Euronorm stacking bins 600 x 400 mm, from a bin height of 120 mm. This takes into account that stacking bins nest slightly into each other. PRO insert bins are easy to remove thanks to **internal grip edges**.

Cases

PRO insert bins are also used in plastic cases **600 x 400 x H 135 mm**. These cases are carried vertically. For this, a lockable lid with an **integrated foam sheet** must be fitted to seal off the insert bins.

TRANSOPLAST
Improves your Logistics

Transoplast
+31(0)314 66 44 00
website@transoplast.com
transoplast.com

Alternative articles



10.3.929.3



30.612.GDH.1

TRANSOPLAST
Improves your Logistics

Transoplast
+31(0)314 66 44 00
website@transoplast.com
transoplast.com