

Article number: 98.120/100.W



Optiflow Freezer Spacer 1200 x 1000 mm



Product specifications

External dimensions (L x W x H)	1200 x 1000 x 35 mm
Material	HDPE
Article number	98.120/100.W
Weight (kg)	3,9 kg
Temperature range	-60°C to +80°C
Static load capacity	7500 kg
Quantity per pallet	150

Properties

Optiflow Freezer Spacers ensure optimum air circulation between stacked boxes.

Thanks to the optimum air circulation, a 40% reduction in freezing time is achieved.

With the Optiflow Freezer Spacer, up to 26% energy can be saved compared to conventional spacers.

Optiflow Freezer Spacers offer a carefully designed support surface. As a result, the packaging is properly supported and does not collapse.

The rigid construction and reinforced support surface of the Optiflow Spacer make stable and high stacking of boxes possible.

Optiflow Freezer Spacers are nestable when unloaded.

The Optiflow Freezer Spacer can be cleaned quickly and easily in a washing machine when nested and in large quantities (100 pieces).

Thanks to small stacking lugs on the top side, boxes do not freeze onto the spacer, and removing the spacers from the boxes is very easy.

The High Performance Optiflow Freezer Spacers qualify for the Energy Investment Allowance (EIA). Ask our product specialists for the details.



Matching accessories



Alternative articles

