Article number: 4307.500.502

Pallet box - 1200 x 1000 x H 400 mm - 260 liter - perforated - 2 skids







Product specifications

External dimensions (L x W x H)	1200 × 1000 × 400 mm
Internal dimensions (L x W x H)	1095 × 895 × 265 mm
Capacity	260 liter
Sidewalls	Perforated
Material	HDPE
Article number	4307.500.502
Weight (kg)	22,5 kg
Temperature range	-30°C to +40°C, briefly up to +90°C
Color	Grey
Bottom	Perforated, reinforced
Max. static stacking load	2000 kg
Max. dynamic stacking load	300 kg
Quantity per pallet	6

Properties

- **Plastic pallet box with perforated walls and perforated base**
- **Format 1200 x 1000 x H 400 mm with a capacity of 260 liter**
- **Version with 2 skids**
- **Stable and robust construction**
- **Good ventilation thanks to the perforated design**
- **Suitable for storage, transport and order picking**
- **Easy to handle with a pallet truck or forklift**
- **Practical low overall height**
- **Suitable for use in logistics, industry, agriculture and production**

TRANSOPLAST
Improves your Logistics

Transoplast
+31(0)314 66 44 00
website@transoplast.com
transoplast.com

Description

This large-volume plastic pallet box has external dimensions of 1200 x 1000 x H 400 mm and a capacity of 260 liter. The internal dimensions are 1095 x 895 x H 265 mm. The pallet box is designed with perforated walls and a perforated base. This makes it particularly suitable for applications where air circulation, water drainage or good visibility of the contents is required.
The version with 2 skids ensures stable positioning and enables easy handling with a pallet truck or forklift. Thanks to its low overall height, the pallet box is particularly practical for lower products or applications where goods need to be stored and picked clearly and efficiently.
The perforated design makes the pallet box versatile in use, for example in industry, logistics, agriculture and production. It offers a robust solution for transport, storage and internal goods movements.

Matching accessories



4410.820.502

Transoplast
+31(0)314 66 44 00
website@transoplast.com
transoplast.com