Article number: 55.QP1210LB9FRS

Plastic export pallet - 1200 x 1000 mm (3 runners) - light version



Product specifications

External dimensions (L x W x H)	1200 × 1000 × 170 mm
Dynamic load capacity	1000 kg
Material	Recycled HDPE
Article number	55.QP1210LB9FRS
Weight (kg)	8,1 kg
Temperature range	-20°C to +60°C
Color	Black
Static load capacity	2500 kg
Quantity per pallet	55

Properties

- **Dimensions: 1200 x 1000 x H 170 mm**
- **Lightweight design**
- **Made from regenerated material**
- **Equipped with 3 pallet runners and rim for additional stability**
- **Suitable for loading with packaged foodstuffs**
- **Static load capacity: 2500 kg**
- **Dynamic load capacity: 1000 kg**

Description

Introducing our nestable plastic export pallet, designed for optimal efficiency and reliability in your logistics operations. Measuring 1200 x 1000 x 170 mm, this pallet boasts a lightweight construction, making it easy to handle and transport while maintaining robustness. Crafted from regenerative materials, it aligns with sustainability goals without compromising on durability.

Equipped with three pallet runners and featuring a rim for added stability, this pallet ensures secure stacking and transportation of goods. Its nestable design allows for efficient storage when not in use, saving valuable space in your warehouse or shipping containers.

Designed to meet the stringent requirements of the food industry, this pallet is suitable for loading with packaged foodstuffs, ensuring hygiene and safety throughout the supply chain. With a static load capacity of 2500 kg and a dynamic load capacity of 1000 kg, it offers reliable performance even under heavy loads, providing peace of mind during transportation and storage.

Invest in our nestable plastic export pallet for a sustainable, efficient, and reliable solution for your logistics needs.

TRANSOPLAST
Improves your Logistics

Transoplast
+31 314 664400
website@transoplast.com
transoplast.com/wp

Alternative articles



57.1208LB9FR

TRANSOPLAST
Improves your Logistics

Transoplast
+31 314 664400
website@transoplast.com
transoplast.com/wp