



Export pallet / ISO container pallet - 1140 x 1140 mm - on 3 runners - open deck - with 5 mm rim all around - standard regrind - black



Product specifications

External dimensions (L x W x H)	1140 x 1140 x 156 mm
Dynamic load capacity	1000 kg
Material	Standard regenerate
Article number	55.QP1140MR3RR
Weight (kg)	15 kg
Temperature range	-20°C to +40°C / briefly up to +90°C
Color	Black
Static load capacity	4000 kg
Edge height	5 mm
Load capacity in racks	250
Quantity per pallet	15

Properties

Plastic pallet type 1140M3 in medium version

Dimensions: 1140 x 1140 x H 156 mm

The dimensions are intended for use in ISO containers (sea containers)

With 3 pallet runners lengthwise

5 mm raised rims all around the pallet deck

Load capacity: static 4000 kg - dynamic 1000 kg - in pallet racking 250 kg

Produced from standard regrind material

Does not absorb moisture and does not develop mould

For trouble-free export to IPPC countries in accordance with ISPM 15

No treatment against unwanted insects and other pests is required

Description

Plastic pallet type 1140M3R (1140 x 1140 x H 156 mm) is mainly used for medium-duty applications in ISO containers (sea containers). The pallet size is ideally suited for this purpose.

The pallet has an open deck with 5 mm raised rims all around. It is also fitted with 3 pallet runners. Produced from standard regrind material.