Article number: 55.QP1140M6RR Printing possible

Export pallet / ISO container pallet - 1140 x 1140 mm - on 6 runners - open deck - with 5 mm rim all around - standard regrind - black



Product specifications

External dimensions (L x W x H)	1140 × 1140 × 156 mm
Dynamic load capacity	1000 kg
Material	Standard regenerate
Article number	55.QP1140M6RR
Weight (kg)	16,3 kg
Temperature range	-20°C to +40°C / briefly up to +90°C
Color	Black
Static load capacity	4000 kg
Load capacity in racks	350
Quantity per pallet	15

Properties

- **Plastic pallet type 1140M6 (1140 x 1140 x H 156 mm) in medium version**
- **The dimensions are intended for use in ISO containers (sea containers)**
- **With 6 pallet runners - runners positioned all around and cross-braced in the centre**
- **5 mm raised rims all around the pallet deck**
- **Load capacity: static 4000 kg - dynamic 1000 kg - in pallet racking 250 kg**
- **Produced from standard regrind material**
- **Does not absorb moisture and does not develop mould**
- **For trouble-free export to IPPC countries in accordance with ISPM 15**
- **No treatment against unwanted insects and other pests is required**

TRANSOPLAST
Improves your Logistics

Transoplast
+31(0)314 66 44 00
website@transoplast.com
transoplast.com

Description

Plastic pallet type 1140M6 (1140 x 1140 x H 156 mm) is mainly used for medium-duty applications in ISO containers (sea containers). The pallet size is ideally suited for this purpose.
The pallet has an open deck with 5 mm raised rims all around. It is also fitted with 6 pallet runners. Produced from standard regrind material.

Transoplast
+31(0)314 66 44 00
website@transoplast.com
transoplast.com