Article number: 55.1212MB3RR Printing possible

Export pallet / drum pallet 1212MB3RR - 1200 x 1200 mm - on 3 runners - with 5 mm raised rim all around - standard regrind - black



Product specifications

External dimensions (L x W x H)	1200 × 1200 × 156 mm
Dynamic load capacity	1375 kg
Material	Standard regenerate
Article number	55.1212MB3RR
Weight (kg)	16,1 kg
Temperature range	-20°C to +40°C / briefly up to +90°C
Color	Black
Static load capacity	4000 kg
Edge height	5 mm
Load capacity in racks	250
Quantity per pallet	15

Properties

- **Plastic pallet type 1212MB3RR in light/medium version (1200 x 1200 mm) for transport and storage of steel drums (e.g. 4 units of 200 liter)**
- **Equipped with 3 pallet runners**
- **With open pallet deck**
- **With 5 mm raised rims around the pallet deck**
- **Load capacity: static 4000 kg - dynamic 1200 kg - in pallet racking 200 kg**
- **Produced from standard regrind material**
- **Does not absorb moisture and does not develop mould**
- **For trouble-free export to IPPC countries in accordance with ISPM 15**
- **No treatment against unwanted insects and other pests is required**
- **Options: version on 6 runners - version with closed deck**

TRANSOPLAST
Improves your Logistics

Transoplast
+31 314 664400
website@transoplast.com
transoplast.com/wp

Description

Plastic pallet type 1212MB3RR (1200 x 1200 x H 156 mm) is mainly used as a drum pallet - for transport and storage of 200 liter steel drums. Four drums of this type fit on this pallet.
The pallet has an open deck with 5 mm raised rims all around. It is also fitted with 3 pallet runners. Produced from standard regrind material.

Alternative articles



55.1212HB3RR

TRANSOPLAST
Improves your Logistics

Transoplast
+31 314 664400
website@transoplast.com
transoplast.com/wp