Article number: 55.QP1212M6RR | Printing possible

Export pallet / drum pallet 1212M6RR - 1200 x 1200 mm - on 6 runners - with 5 mm raised rim all around - standard regrind - black



Product specifications

External dimensions (L x W x H)	1200 × 1200 × 156 mm
Dynamic load capacity	1200 kg
Material	Standard regenerate
Article number	55.QP1212M6RR
Weight (kg)	17,5 kg
Temperature range	-20°C to +40°C / briefly up to +90°C
Color	Black
Static load capacity	4000 kg
Load capacity in racks	200
Quantity per pallet	15

Properties

- **Plastic pallet type 1212M6RR in light/medium version (1200 x 1200 mm) for transport and storage of steel drums (e.g. 4 units of 200 liter)**
- **Equipped with 6 pallet runners**
- **With open pallet deck**
- **With 5 mm raised rims all around the pallet deck**
- **Load capacity: static 4000 kg - dynamic 1200 kg - in pallet racking 200 kg**
- **Produced from standard regrind material**
- **Does not absorb moisture and does not develop mould**
- **For trouble-free export to IPPC countries in accordance with ISPM 15**
- **No treatment against unwanted insects and other pests is required**
- **Options: version on 3 runners - version with closed deck**

TRANSOPLAST
Improves your Logistics

Transoplast
+31(0)314 66 44 00
website@transoplast.com
transoplast.com

Description

Plastic pallet type 1212M6RR (1200 x 1200 x H 156 mm) is mainly used as a drum pallet - for transport and storage of 200 liter steel drums. Four drums of this type fit on this pallet.
The pallet has an open deck with 5 mm raised rims all around. It is also fitted with 6 pallet runners. Produced from standard regrind material.

Transoplast
+31(0)314 66 44 00
website@transoplast.com
transoplast.com