Article number: 55.QP1212M6RR Printing possible

# Export pallet / drum pallet 1212M6RR - 1200 x 1200 mm - on 6 runners - with 5 mm raised rim all around - standard regrind - black



## Product specifications

| | |
|---|---|
| External dimensions ( L x W x H) | 1200 × 1200 × 156 mm |
| Dynamic load capacity | 1200 kg |
| Material | Standard regenerate |
| Article number | 55.QP1212M6RR |
| Weight (kg) | 17,5 kg |
| Temperature range | -20°C to +40°C / briefly up to +90°C |
| Color | Black |
| Static load capacity | 4000 kg |
| Load capacity in racks | 200 |
| Quantity per pallet | 15 |

## Properties

- **Plastic pallet type 1212M6RR in light/medium version (1200 x 1200 mm) for transport and storage of steel drums (e.g. 4 units of 200 liter)**
- **Equipped with 6 pallet runners**
- **With open pallet deck**
- **With 5 mm raised rims all around the pallet deck**
- **Load capacity: static 4000 kg - dynamic 1200 kg - in pallet racking 200 kg**
- **Produced from standard regrind material**
- **Does not absorb moisture and does not develop mould**
- **For trouble-free export to IPPC countries in accordance with ISPM 15**
- **No treatment against unwanted insects and other pests is required**
- **Options: version on 3 runners - version with closed deck**

TRANSOPLAST
Improves your Logistics

**Transoplast**
+31 314 664400
website@transoplast.com
transoplast.com/wp

# Description

Plastic pallet type 1212M6RR (1200 x 1200 x H 156 mm) is mainly used as a drum pallet - for transport and storage of 200 liter steel drums. Four drums of this type fit on this pallet.
The pallet has an open deck with 5 mm raised rims all around. It is also fitted with 6 pallet runners. Produced from standard regrind material.



**Transoplast**
+31 314 664400
website@transoplast.com
transoplast.com/wp