Article number: 55.QP6080L3RR

Export pallet / display pallet 6080L3RR - 800 × 600 mm - 3 pallet runners (crosswise) - 5 mm rim - nestable - standard recycled material - black



Product specifications

External dimensions (L x W x H)	800 × 600 × 145 mm
Dynamic load capacity	350 kg
Material	Standard regenerate
Article number	55.QP6080L3RR
Weight (kg)	2,5 kg
Temperature range	-20°C to +40°C
Color	Black
Static load capacity	500 kg
Edge height	5 mm
Quantity per pallet	100

Properties

- **Plastic pallet 800 x 600 mm in half Euro size**
- **Nestable design on 3 pallet runners crosswise - space-saving**
- **Light/medium version made from standard regrind**
- **Lightweight, stable and easy to handle**
- **Ideal for goods export (also for packaged food products)**
- **Also widely used for display applications in the retail sector**
- **Does not absorb moisture and does not develop mould**
- **For trouble-free export to IPPC countries in accordance with ISPM 15**
- **Options: version on 6 feet medium - version on 6 feet heavy**

Description

Plastic pallet designed to be fully nestable, including the runners. Intended to save volume and costs during delivery and when storing empty pallets. Our plastic pallet 6080 is widely used as an export pallet for light to medium-duty applications. In addition, the pallet is often used as a display pallet for in-store presentations in wholesale and retail. A special application is its use as a tyre pallet for storing tyre sets (often with rims) in tyre hotels. For this purpose, we supply matching cover plates and lashing straps. The complete set is delivered together.

TRANSOPLAST
Improves your Logistics

Transoplast
+31 314 664400
website@transoplast.com
transoplast.com/wp

TRANSOPLAST
Improves your Logistics

Transoplast
+31 314 664400
website@transoplast.com
transoplast.com/wp