

Article number: 55.QP6080L3RR



# Export pallet / display pallet 6080L3RR

## - 800 × 600 mm - 3 pallet runners (crosswise) - 5 mm rim - nestable - standard recycled material - black



### Product specifications

External dimensions ( L x W x H) 800 x 600 x 145 mm

Dynamic load capacity 350 kg

Material Standard regenerate

Article number 55.QP6080L3RR

Weight (kg) 2,5 kg

Temperature range -20°C to +40°C

Color Black

Static load capacity 500 kg

Edge height 5 mm

Quantity per pallet 100

### Properties

Plastic pallet 800 x 600 mm in half Euro size

Nestable design on 3 pallet runners crosswise - space-saving

Light/medium version made from standard regrind

Lightweight, stable and easy to handle

Ideal for goods export (also for packaged food products)

Also widely used for display applications in the retail sector

Does not absorb moisture and does not develop mould

For trouble-free export to IPPC countries in accordance with ISPM 15

Options: version on 6 feet medium - version on 6 feet heavy

### Description

Plastic pallet designed to be fully nestable, including the runners. Intended to save volume and costs during delivery and when storing empty pallets. Our plastic pallet 6080 is widely used as an export pallet for light to medium-duty applications. In addition, the pallet is often used as a display pallet for in-store presentations in wholesale and retail. A special application is its use as a tyre pallet for storing tyre sets (often with rims) in tyre hotels. For this purpose, we supply matching cover plates and lashing straps. The complete set is delivered together.

