
Article number: 83320801.DUOL3S Printing possible

Plastic pallet D3-DUO - 2400 x 1000 mm - with rims 7 mm - 3 pallet runners - reinforced





TRANSOPLAST
Improves your Logistics

Transoplast
+31 314 664400
website@transoplast.com
transoplast.com/wp

Product specifications

External dimensions (L x W x H)	2400 × 1000 × 150 mm
Dynamic load capacity	1000 kg
Material	HDPE
Article number	83320801.DUOL3S
Weight (kg)	34,5 kg
Temperature range	-30°C to +40°C, briefly up to +90°C
Color	Grey
Static load capacity	5000 kg

Properties

- **Large-format plastic pallet size 2400 x 1000 x H 150 mm**
- **Made from high quality virgin HDPE plastic, exceptionally impact-resistant and durable**
- **Suitable for food products**
- **The D3 DUO is based on the D3 pallet, with rims 7 mm (alternative: without rims)**
- **In this version, two D3 pallets are sustainably welded together**
- **The D3 DUO pallet is equipped with 3 pallet runners lengthwise**
- **The deck is additionally reinforced with 3 integrated reinforcement profiles in the longitudinal direction and 2 across; corrosion-resistant design**
- **Extremely strong and robust, making it the ideal solution for large-format loads**
- **RFID technology can be integrated into the pallet without any issues, even retrofitted. The RFID tag holder provides long-lasting protection against external influences**
- **D3 pallet runners are chamfered on both sides for smooth handling with pallet trucks**
- **The D3 pallet is extra strong thanks to an angled connection between the pallet runners and the blocks**
- **This minimises breakage at these sensitive points**
- **The stated dynamic load is based on an evenly distributed load and a wide forklift tine position**

Description

Plastic large-format pallet (2400 x 1000 x H 150 mm), type D3, made from impact resistant new HDPE plastic. Based on two pallets of type D3, which are sustainably welded together. Equipped with 3 pallet runners longitudinally, underside with blocks and pallet runners open (ribbed). Upper deck with rims 7 mm. The top deck is supplied as standard with 3 reinforcement profiles in the longitudinal direction and 2 across. Static load capacity is 5000 kg and dynamic load capacity 1000 kg. Maximum dynamic load of 1000 kg with evenly distributed load and a wide forklift tine position. Also available in a version without rims on the top deck. Various organisations use large-format pallets to their full satisfaction.

General

The dimensions of custom-made pallets are aligned with the customer’s requirements as much as possible. However, the existing pallet construction is decisive for the welding work. As a result, the achievable dimensions may deviate by a few centimetres.

Transoplast
+31 314 664400
website@transoplast.com
transoplast.com/wp