


Article number: 83325201.DUOL3

Printing possible



# Plastic pallet D3-DUO ECO - 2340 x 1000 mm - with 7 mm rims all around - 3 pallet runners - reinforced



## Product specifications

External dimensions ( L x W x H)	2340 x 1000 x 150 mm
Dynamic load capacity	1000 kg
Material	Recycled ECO-HDPE
Article number	83325201.DUOL3
Weight (kg)	32,5 kg
Temperature range	-30°C to +40°C, briefly up to +90°C
Color	Black
Static load capacity	5000 kg
Edge height	7 mm

## Properties

**Large-format plastic pallet size 2340 x 1000 x H 150 mm**

**Made from ECO regranulate, exceptionally impact-resistant and durable**

**Suitable for non-food items and packed food products**

**The D3-DUO ECO is based on the D3 ECO pallet, with 7 mm rims all around (alternative: without rims)**

**In this version, two D3 ECO pallets are sustainably welded together**

**The D3-DUO pallet is equipped with 3 pallet runners lengthwise**

**The deck is additionally reinforced with 4 integrated reinforcement profiles in the longitudinal direction; corrosion-resistant design**

**Extremely strong and robust, making it the ideal solution for large-format loads**

**RFID technology can be integrated into the pallet without any issues, even retrofitted. The RFID tag holder provides long-lasting protection against external influences**

**D3 pallet runners are chamfered on both sides for smooth handling with pallet trucks**

**The raised rims around the D3 prevent the load from sliding off and prevent empty pallets from shifting against each other**

**The D3 pallet is extra strong thanks to an angled connection between the pallet runners and the blocks**

**This minimises breakage at these sensitive points**

**The stated dynamic load is based on an evenly distributed load and a wide forklift tine position**

## Description

Plastic large-format pallet (2340 x 1000 x H 150 mm), type D3-DUO ECO, made from robust ECO regranulate. Based on two pallets of type D3 ECO, which are sawn and then sustainably welded together. Equipped with 3 pallet runners longitudinally, underside with blocks and pallet runners open (ribbed). With 7 mm rims all around. The top deck is supplied as standard with 4 reinforcement profiles in the longitudinal direction. Static load capacity is 5000 kg and dynamic load capacity 1000 kg. Maximum dynamic load of 1000 kg with evenly distributed load and a wide forklift tine position. Also available in a version without rims on the top deck. Various organisations use large-format pallets to their full satisfaction.

### General

The dimensions of custom-made pallets are aligned with the customer's requirements as much as possible. However, the existing pallet construction is decisive for the welding work. As a result, the achievable dimensions may deviate by a few centimetres.

## Alternative articles

