


Article number: 83525861.DUO

Printing possible



# Plastic pallet E3-DUO ECO - 2000 x 1000 mm - with 5 mm rims all around - 3 pallet runners - reinforced



## Product specifications

External dimensions ( L x W x H)	2000 x 1000 x 160 mm
Dynamic load capacity	1250 kg
Material	Recycled ECO-HDPE
Article number	83525861.DUO
Weight (kg)	40 kg
Temperature range	-30°C to +40°C, briefly up to +90°C
Color	Grey
Static load capacity	7500 kg
Edge height	5 mm

## Properties

**Large-format plastic pallet size 2000 x 1000 x H 160 mm**

**Made from ECO regranulate, exceptionally impact-resistant and durable**

**Suitable for non-food items and packed food products**

**The E3-DUO ECO is based on the E3 ECO pallet, with 5 mm rims all around (alternative: without rims)**

**In this version, two E3 ECO pallets are sustainably welded together**

**The E3-DUO pallet is equipped with 3 pallet runners lengthwise**

**The deck is additionally reinforced with 3 integrated reinforcement profiles lengthwise; corrosion-resistant design**

**Extremely strong and robust, making it the ideal solution for large-format loads**

**RFID technology can be integrated into the pallet without any issues, even retrofitted. The RFID tag holder provides long-lasting protection against external influences**

**E3 pallet runners are chamfered on both sides for smooth handling with pallet trucks**

**The raised rims around the E3 prevent the load from sliding off and prevent empty pallets from shifting against each other**

**The E3 pallet is extra strong thanks to an angled connection between the pallet runners and the blocks**

**This minimises breakage at these sensitive points**

**The stated dynamic load is based on an evenly distributed load and a wide forklift tine position**

## Description

Plastic large-format pallet (2000 x 1010 x H 160 mm), type E3-DUO ECO, made from robust ECO regranulate. Based on two pallets of type E3 ECO, which are sawn and then sustainably welded together. Equipped with 3 pallet runners longitudinally, underside with blocks and pallet runners open (ribbed). With 5 mm rims all around. The top deck is supplied as standard with 3 reinforcement profiles in the longitudinal direction (option: 4 longitudinal profiles). Static load capacity is 7500 kg and dynamic load capacity 1250 kg. Maximum dynamic load of 1250 kg (1500 kg with 4 reinforcement profiles) with evenly distributed load and a wide forklift tine position. Also available in a version without rims on the top deck. Various organisations use DUO pallets to their full satisfaction.

### General

The dimensions of custom-made pallets are aligned with the customer's requirements as much as possible. However, the existing pallet construction is decisive for the welding work. As a result, the achievable dimensions may deviate by a few centimetres.

## Alternative articles