
Article number: 87035241.DUOL1 Printing possible

Plastic pallet TC3-DUO ECO - 2000 x 1000 mm - with 7 mm rims all around - 3 pallet runners







Transoplast
+31(0)314 66 44 00
website@transoplast.com
transoplast.com

Product specifications

External dimensions (L x W x H)	2000 × 1000 × 160 mm
Dynamic load capacity	1000 kg
Material	Recycled HDPE
Article number	87035241.DUOL1
Weight (kg)	38 kg
Temperature range	-30°C to +40°C, briefly up to +90°C
Color	Black
Static load capacity	7500 kg
Edge height	7 mm

Properties

- **Large-format plastic pallet size 2000 x 1000 x H 160 mm**
- **Made from ECO regranulate, exceptionally impact-resistant and durable**
- **Suitable for non-food items and packed food products**
- **The TC3-DUO ECO is based on the TC3 ECO pallet, with 7 mm rims all around (alternative: without rims)**
- **In this version, two TC3 ECO pallets are sustainably welded together**
- **The TC3-DUO pallet is equipped with 3 pallet runners in the longitudinal direction**
- **Extremely strong and robust, making it the ideal solution for large-format loads**
- **TC3 pallet runners are chamfered on both sides for smooth handling with pallet trucks**
- **The raised rims around the TC3 prevent the load from sliding off and prevent empty pallets from shifting against each other**
- **The TC3 pallet is extra strong thanks to an angled connection between the pallet runners and the blocks**
- **This minimises breakage at these sensitive points**
- **The stated dynamic load is based on an evenly distributed load and a wide forklift tine position**

Description


Plastic large-format pallet (2000 x 1000 x H 160 mm), type TC3-DUO ECO, made from robust ECO regranulate. Based on two pallets of type TC3 ECO, which are sawn and then sustainably welded together. Equipped with 3 pallet runners in the longitudinal direction, underside with blocks and pallet runners closed. With 7 mm rims all around. Static load capacity is 7500 kg and dynamic load capacity 1250 kg. Maximum dynamic load of 1250 kg with evenly distributed load and a wide forklift tine position. Also available in a version without rims on the top deck. Various organisations use DUO pallets to their full satisfaction.

General

The dimensions of custom-made pallets are aligned with the customer’s requirements as much as possible. However, the existing pallet construction is decisive for the welding work. As a result, the achievable dimensions may deviate by a few centimetres.

Transoplast
+31(0)314 66 44 00
website@transoplast.com
transoplast.com

Alternative articles



83335202



87035841.DUO



87035241



87035841

TRANSOPLAST
Improves your Logistics

Transoplast
+31(0)314 66 44 00
website@transoplast.com
transoplast.com