
Article number: 30.125.0117 Printing possible

# Stacking crate - 600 x 400 x H 250 mm - fully perforated - 4 open handgrips - grid base - orange







## Product specifications

| | |
|---|---|
| External dimensions ( L x W x H) | 600 × 400 × 250 mm |
| Internal dimensions (L x W x H) | 568 × 368 × 234 mm |
| Capacity | 48.9 liter |
| Handles | Open (four openings) |
| Sidewalls | Perforated |
| Material | HDPE |
| Article number | 30.125.0117 |
| Weight (kg) | 1,8 kg |
| Temperature range | -30°C to +40°C, briefly up to +90°C |
| Color | Orange |
| Bottom | Perforated, reinforced (base implementation no. 15) |
| Colorcode | PMS 137 C |
| Quantity per pallet | 36 |
| Stacking height (mm) | 240 |

## Properties

- **Practical orange stacking crate from the BASIC BREAD LINE. Dimensions 600 x 400 x H 250 mm**
- **Fully perforated - both the walls and the base**
- **Generous perforations for maximum ventilation of the contents - helping to reduce condensation and mould formation**
- **High stability thanks to strategically positioned reinforcements in the walls and base construction**
- **Fitted with four open handgrips for easy handling**
- **Thanks to the Euronorm format, easily stackable with other Euronorm bins and crates and compatible with standardised mobile plastic trolleys and pallets**
- **Prepared for the use of compartment dividers made from separate elements - in the handgrips and on the base**
- **Food-safe and hygienically designed**
- **Options: printing (short sides) - loose-fit lid - coversheets**

TRANSOPLAST
Improves your Logistics

**Transoplast**
+31 314 664400
website@transoplast.com
transoplast.com/wp

## Description

Practical stacking crate in Euronorm format (600 x 400 x H 250 mm). Finished in **orange** and part of our widely used **BASIC BREAD LINE** for the **bakery sector**.

The stacking crate features **generous perforations** in both the walls and the base. This ensures **optimal ventilation**, allowing the contents to 'breathe' and any condensation to drain away quickly. As the **stability** of the crate is also important, the walls have been reinforced at strategic points and the wall perforations are arranged in a smart and proven grid pattern. Special attention has also been given to **base reinforcement**. The open base is reinforced on the underside with a **very robust grid**, with perforations designed as T-profiles. This strong construction results in a particularly robust crate with a high load capacity, while remaining relatively lightweight and easy to handle.

Thanks to its **standardised dimensions** (600 x 400 mm), the stacking crate can be stacked with all other **Euronorm stacking bins and crates** and is perfectly compatible with **standardised pallets**, **mobile plastic trolleys** and **roll containers**. This makes logistics particularly efficient and helps prevent unnecessary loss of space.

**Application**

Thanks to the **generous perforations**, the stacking crate is widely used for **bakery products**, as well as many other foodstuffs. These products need to '**breathe**' to help prevent mould formation. Our **BASIC BREAD LINE** is an excellent choice for these applications.

Another advantage of the generous perforations is the high **visibility** of the contents. Products inside the crate can therefore be identified easily. This also makes our BASIC BREAD LINE crates highly suitable for **warehouse applications** in the bakery sector.

## Matching accessories



30.600.OD.1



99.CVSH.600



58.TL6040.4.K



89.E3

## Alternative articles



30.125.0105.15



30.125.5x8.UO



83100801



83180801



52.RC682D.ZABV.2

**Transoplast**
+31 314 664400
website@transoplast.com
transoplast.com/wp