Article number: 30.013.19.4 Printing possible

# Stacking crate - 400 x 300 x H 142 mm - fully perforated - open handgrips - reinforced base - red





## Product specifications

| | |
|---|---|
| External dimensions ( L x W x H) | 400 × 300 × 142 mm |
| Internal dimensions (L x W x H) | 372 × 272 × 129 mm |
| Capacity | 13 liter |
| Handles | Open (two openings) |
| Sidewalls | Perforated |
| Material | HDPE |
| Article number | 30.013.19.4 |
| Weight (kg) | 0,74 kg |
| Temperature range | -30°C to +40°C, briefly up to +90°C |
| Color | Red |
| Bottom | Perforated, reinforced (base implementation no. 19) |
| Quantity per pallet | 128 |
| Stacking height (mm) | 130 |

## Properties

- **Robust stacking crate from the RX series. Dimensions 400 x 300 x H 142 mm**
- **Suitable for a wide range of applications: industry and craft sectors, as well as the fruit and vegetable sector and food processing**
- **Fully perforated - both the walls and the base**
- **With open handgrips for a comfortable grip**
- **The base is reinforced for optimal load capacity**
- **Food-safe and hygienically designed**
- **Fitted with a label holder on all 4 sides**
- **Options: loose-fit lid, coversheets, printing**

TRANSOPLAST
Improves your Logistics

**Transoplast**
+31 314 664400
website@transoplast.com
transoplast.com/wp

## Description

Robust plastic stacking crate in **Euronorm format (400 x 300 x H 142 mm** - 13 liter) and part of our **RX series** - a product range used in a wide variety of applications. Users are found in industry and craft sectors, as well as in the fruit and vegetable sector and food processing.

Thanks to the **standardised dimensions** (400 x 300 mm), the stacking crate is **stackable with all other Euronorm stacking crates and bins**. The crate is **fully perforated**, meaning both the walls and the base are perforated. This allows rainwater to drain away easily.

The stacking crate is food-safe, has a **hygienic design** and is fitted with two practical open handgrips. The base is **reinforced on the underside** for optimal load capacity.

## Matching accessories



30.400.OD.1



52.RC682D.ZABV.2



99.CVSH.400

**Transoplast**
+31 314 664400
website@transoplast.com
transoplast.com/wp